

Nedland NC-50 Comparison Chart

	NC-50	MINI-MAX
Charge Box Capacity	• .5 cu.Yd.	.39 cu. Yd.
Ram Penetration	4"	4"
Ram Force	• 21,000 lbs	16,400 lbs
Pump	• 5 GPM	3 GPM
Motor	• 5 HP	3 HP
Cylinders	• Twin By-pass cylinders 2.5" X 20" X 1.5"	Twin standard cylinders 2.5" X 18" X 1.25"
Controls	• 15' Remote	No Remote
	• 80% Full light	N/A
	• 100 % Full Light	100% Full Light
	• Multi Cycle Timer	N/A
	• Key Lock Start	Key Lock Start
	• Forward/Reverse	Forward/Reverse
	• Emergency Stop	Emergency Stop
	• Low Oil Shutdown	N/A
	• Automatic Shutdown	N/A
	Other	• Fluid Level/Temp Gauge
• Pressure Gauge		N/A
• Inlet Fluid Strainer		N/A
Container Attachment	• Single Side Lever System	Two Small Ratchet Binders
Hydraulic Oil	• 35 Gallon	10 Gallon
	• Biodegradable	Standard
	• ½" Impact Plate	None
Hopper	• None	Standard Valve
Directional Valve	• None	Standard Valve
Packing Blade	• Neoprene Wear Strips	None
	• Rides on Neoprene	Rides on Steel
	• 8:1	4:1
Compaction Ratio	• 8:1	4:1
Weight	• 2900 lbs	1600 lbs
Warranty	• 5-3-1 Year	6 months/1 year

• Indicates Superior Specifications